

# Huawei Auto-transformer



## Simple & Easy

- Designed to be connected to Huawei inverter for all sizes, needed for backup applications
- Simply wiring, supports easy installation on the wall

## Safe & Reliable

- Protection rating: TYPE 4X, supports outdoor application
- Natural convection, supports thermal protection

Technical Specification	HW-TX-5000
<b>Electrical Ratings</b>	
Continuous rated power	5 kVA
Output voltage	120 / 240 V Split Phase
Max continuous output current per phase @ 120 V	32 A
Rated AC grid frequency	60 Hz
<b>Standard Compliance</b>	
Safety	UL 5085-1, UL 5085-2
<b>General Specification</b>	
Dimensions (W x H x D)	10.4 in x 11.0 in x 5.5 in (265 mm x 280 mm x 140 mm)
Weight	28.7 lb. (13.0 kg)
Operating temperature	-40°C ~ 45°C (-40°F ~ 113°F)
Humidity range	0 ~ 100 % RH
Protection rating	TYPE 4X
Cooling	Natural convection
Noise emission	≤25 dB (A)
Installation	Wall mounted
AC output conduit size	0.75" Conduit

The text and figures reflect the current technical state at the time of printing. Subject to technical changes. Errors and omissions excepted. Huawei assumes no liability for mistakes or printing errors. For more information, please visit solar.huawei.com. Version No.01-(2018828)